

AC PROTECTION

ACP-1 - SINGLE OUTLET AC SURGE PROTECTOR WITH GROUND LUG

Features:

- Single outlet AC protection
- Direct Plug-in
- Diagnostic indicator lights
- EMI/RFI noise filtration
- **Lifetime Product Warranty** - This surge protector shall be free of any defects in design, materials, or workmanship, or ITW Linx will repair or replace the defective product.



ORDERING INFORMATION

ITW Linx Part Number	Description
ACP-1	One outlet surge protector, UL primary or secondary single point ground, not to exceed 6-pairs. (MOQ 5)

* Questions about ordering? Please contact us at **1-800-336-LINX** / Contact an authorized distributor for pricing *



For up-to-date warranty information, please visit our web site at www.itwlinx.com.

TECHNICAL SPECIFICATIONS

PRODUCT SPECIFICATIONS:

Agency Approval	UL 1449
LED Indicators	Yes
Grounding Requirements	Uses Electrical AC Ground
Ground Impedance	N/A
Width	1.88"
Height	2.62"
Depth	0.38"
Weight	0.04 lbs
Product Warranty	Lifetime
Connected Equipment Warranty	N/A

SIGNAL LINE SURGE PROTECTION:

TELCO CIRCUIT PROTECTION	N/A
COAX CIRCUIT PROTECTION	N/A
LAN CIRCUIT PROTECTION	N/A

AC SURGE PROTECTION:

SurgeGate Plus Circuitry	N/A
Thermal Fusing	Yes
Catastrophic Surge Circuit	Yes
Over/Undervoltage Voltage Protection	N/A
Over/voltage Voltage Shutoff	N/A
Undervoltage Voltage Shutoff	N/A
Single Pulse Energy Dissipation	1350 Joules
Peak Impulse Current	52,000 A
EMI/RFI Noise Filtration	50dB (99.7%)
Line Voltage	120V (50/60Hz)
Initial Clamping Level	200V Peak, 141 Rms
Maximum Current Rating	15A (1800W)
Response Time	1-5 Nanoseconds
Plug Configuration	Direct Plug-in
Number of Outlets	1

For more technical information, refer to "TECHNICAL REFERENCE", page(81-98).

Signal Perfect™ - For more information, refer to page 81.



UltraLinx™

