

# AC PROTECTION

## M2 - ADVANCED SERIES 2-OUTLET DIRECT PLUG-IN SURGE PROTECTOR

### Features:

- 2-outlet AC protection
- Direct Plug-in
- Diagnostic indicator lights (2)
- EMI/RFI noise filtration
- Integrated cable management
- Enhanced Backlight
- **Lifetime Product Warranty** - This surge protector shall be free of any defects in design, materials, or workmanship, or ITW Linx will repair or replace the defective product.



### ORDERING INFORMATION

ITW Linx Part Number	Description
M2	2-outlet AC surge protector, with Protect or Disconnect circuitry and integrated cable management. (MOQ 24)

\* Questions about ordering? Please contact us at **1-800-336-LINX** / Contact an authorized distributor for pricing \*



For up-to-date warranty information, please visit our web site at [www.itwlinx.com](http://www.itwlinx.com).

### TECHNICAL SPECIFICATIONS

#### PRODUCT SPECIFICATIONS:

Agency Approval .....	UL 1363, 1449
LED Indicators .....	2
Grounding Requirements .....	Uses Electrical AC ground,
Width .....	3.5"
Height .....	5.5"
Depth .....	2"
Weight .....	0.74 lbs
Product Warranty .....	Lifetime

#### SIGNAL LINE SURGE PROTECTION:

TELCO CIRCUIT PROTECTION .....	N/A
COAX CIRCUIT PROTECTION .....	N/A
LAN CIRCUIT PROTECTION .....	N/A

#### AC SURGE PROTECTION

Thermal Fusing .....	Yes
Catastrophic Surge Circuit .....	Yes
Single Pulse Energy Dissipation .....	1350 Joules
Peak Impulse Current .....	52,000 A
EMI/RFI Noise Filtration .....	50db (99.7%)
Line Voltage .....	120V (50/60Hz)
Initial Clamping Level .....	200V Peak, 141 Rms
UL 1449 Rating .....	400V
Protection Modes .....	L-N, L-G, N-G
Maximum Current Rating .....	15A (1800W)
Response Time .....	1-5 Nanoseconds
Plug Configuration .....	Direct Plug-in
Number of Outlets .....	2
Switched Outlets .....	N/A
Cord Length .....	N/A

For more technical information, refer to "TECHNICAL REFERENCE", page(81-98).

**Signal Perfect™** - For more information, refer to page 81.



# M2 Series

