

MODULAR PROTECTION

MCO4X4 - ANALOG STATION SET AND CENTRAL OFFICE LINE PROTECTOR



Features:

- **Auto-Resetting Technology** - PTC resistors open when a surge occurs, protecting your equipment, but unlike other fuses, the PTCs close again once the surge passes. Less downtime, and less service calls.
- **Expandable System Protection** - SurgeGate Series Base Units and Modules can be attached to expand system protection as your system grows.
- **Lifetime Product Warranty** - This surge protector shall be free of any defects in design, materials, or workmanship, or ITW Linx will repair or replace the defective product.
- **\$50,000 Connected Equipment** - This ITW Linx product will protect your equipment or we will repair or replace it up to \$50,000!
- **AVAYA** approved product: 146C, 407228923

ORDERING INFORMATION

ITW Linx Part Number	Description
MCO4X4	Protects up to 2-wires (1-pair) per jack using RJ-11/45 connectors (pins 4, 5). (MOQ 6)

* Questions about ordering? Please contact us at **1-800-336-LINX** / Contact an authorized distributor for pricing *



For up-to-date warranty information, please visit our web site at www.itwlinx.com.

TECHNICAL SPECIFICATIONS

PRODUCT SPECIFICATIONS:

Agency Approval	UL 497A (Secondary)
LED Indicators	N/A
Grounding Requirements	Uses Electrical AC Ground
.....for use with SurgeGate Series AC Base Units.	
..... See Technical Reference page 81-98 for additional grounding tips.	
Recommended Grounding Impedance.....	<0.5 Ohm
Width.....	4.25"
Height.....	4.25"
Depth	1.5"
Weight.....	0.43 lbs
Product Warranty.....	Lifetime
Connected Equipment Warranty.....	Up to \$50,000

SIGNAL LINE SURGE PROTECTION:

TELCO CIRCUIT PROTECTION

Signal Perfect Circuitry	Yes
Auto-Resetting PTCs	160 mA (8-10 Ohms)
Clamping Level	260V (T-R, T-G, R-G)
Response Tim	1-5 Nanoseconds
Capacitance.....	<50pF
Suppression Modes	Metallic & Longitudinal
Wires Protected	4-wires (1-pair) per jack (pins 3, 6 & 4, 5)
Termination Type	RJ-11/45

For more technical information, refer to "TECHNICAL REFERENCE", page(81-98).

AC SURGE PROTECTION:

SurgeGate Plus Circuitry	N/A
Thermal Fusing.....	N/A
Catastrophic Surge Circuit	N/A
Over/Undervoltage Voltage Protection	N/A
Overvoltage Voltage Shutoff	N/A
Undervoltage Voltage Shutoff	N/A
Single Pulse Energy Dissipation	N/A
Peak Impulse Current.....	N/A
EMI/RFI Noise Filtration.....	N/A
Line voltage.....	N/A
Initial Clamping Level.....	N/A
UL 1449 Rating.....	N/A
Protection Modes.....	N/A
Maximum Current Rating	N/A
Response Time	N/A
Plug Configuration	N/A
Number of Outlets.....	N/A
Switched Outlets.....	N/A
Cord Length.....	N/A

This product also for use with these systems:

NEC • PANASONIC • COMDIAL • VODAVI • SIEMENS • MITEL

For more information, refer to "TELEPHONE SYSTEM CONFIGURATORS", (page 82-85).

Signal Perfect™ - For more information, refer to page 81.



SurgeGate™

