


CABLE MANAGEMENT

TAP-IN - SECURELY FASTEN WIRES TO CONCRETE AND OTHER HARD SURFACES



Features:

- Route wires along concrete, brick, mortar, cinder blocks and other hard surfaces - without drilling.
- Two specially-hardened drive pins securely fasten wires and prevent cord rotation.
- Install in seconds with only a hammer.
- Integral strain relief grips to hold clips on wire - no need to hold clip while installing it.
- Small, aesthetically pleasing and won't interfere with décor. Clear versions are virtually invisible.
- Weather-proof, ultraviolet (UV) stabilized material protects against deterioration.
- Insulated to protect against shorts during installation / removal.
- Longer pins (LP) are available for soft, porous materials like mortar, cinder block, stucco and wood.

ORDERING INFORMATION

ITW Linx Part Number	Cable Type	Cable Diameter	Color	Pin Length (driven)	Mechanical
TA-1 TA-1LP	2 & 3 Pair or ground wire	0.13" - 0.18" 0.13" - 0.18"	Clear Clear	0.12" 0.12"	
TA-3	RG-6 or RG-59	0.25" - 0.33"	Clear	0.27"	
<i>(Above products have to be purchased of minimum 5000)</i>					
TA-5	Quad Shielded RG-11 or 25-pair PBX cable	0.35" - 0.40"	Clear	0.133"	
TA-6	Quad Shielded RG-11 or 25-pair PBX cable for corners	0.25" - 0.33"	Clear	0.27"	
<i>(Above products have to be purchased of minimum 3200)</i>					
TA-7** TA-7HPP** TA-7HPPC**	RG-59	0.20" - 0.26"	Black	0.33" 0.52" 0.52"	
TA-8**	Quad Shielded RG-6	0.13" - 0.18"	Black	0.33"	
TA-9** TA-9LP**	2 and 3-pair or ground wire	0.11" - 0.17" 0.11" - 0.17"	Black Black	0.28" 0.40"	
TA-10	Drop wire	0.28" - 0.34"	Clear	0.25"	
<i>(TA-10 has to be purchased of minimum 4800)</i>					
TA-11** TA-11HPP**	RG-59 or RG-6	0.25" - 0.31" 0.25" - 0.31"	Black Black	0.33" 0.52"	
TA-12	4-pair	0.15" - 0.22"	Clear	0.25"	
<i>(TA-12 has to be purchased of minimum 5000)</i>					

** Part numbers are special order. Contact us at 1-800-336-LINX for pricing, minimum of quantity and availability.

Tap-Ins™

